



DIRECTUPS

XP 400/600

Line Interactive UPS

DESIGN TO PROTECT YOUR PC AND MULTI-DEVICES

- *Microprocessor Controlled guarantees high reliability*
- *Internet Ready: Protection for Modem/Phone Line*
- *Smart Short Circuit and Overload Protection*
- *Intelligent Battery Management*
- *User-Replaceable Battery Design*
- *Surge protected outlets available for convenience*
- *Audible warning reminds users of abnormal condition*
- *Easy understanding LED display*



BEST POWER PROTECTION

Wiring Fault LED
Instantly alerts you to dangerous fault outlet wiring at your facility.

UPS Status LED
Green LED lights on when AC utility is normal; Green LED flashes when AC utility fails and UPS is providing power to your equipment.

Fault LED
Shows you any faults occur such as UPS fault, and battery fault.

Modem/Phone Line Surge Protection
It maintains your Internet without interruption.

AC Input
Its the other end plug into the AC utility to offer full protection for your system.

Power On/Off
AC Mode: Green LED on
Battery Mode: Green LED flashing

Surge Protected ONLY Receptacles
All receptacles offer protection against lightning, surges, spikes and noises.

Battery Power Supplied Receptacles
All plugged equipment is powered by batteries while AC failure.

Widely - Spaced Receptacles
It accepts any size transformer blocks without blocking access to other receptacles.

Hot-swappable Battery Design
This feature helps users replace batteries easily.

Other features shown: Fax, Scanner, Printer

XP UPS SPECIFICATION

MODEL		XP 400	XP 600
CAPACITY	VA/W	400VA / 200W	600VA / 300W
INPUT	Voltage	120VAC	
	Frequency	47 - 63Hz	
	Phase	Single	
OUTPUT (Inverter Mode)	Voltage Range	120VAC \pm 10%	
	Frequency	50Hz or 60Hz \pm 1Hz	
	Waveform	Modified Sinewave	
TRANSFER TIME	Typical	4ms	
BATTERY	Battery Type	6V/4Ah	12V/5Ah
	Battery Number	2	1
	Recharging Time	8 hours up to 90%	
	Backup Time (at a PC load with PII and 15" monitor)	10 minutes	20 minutes
DISPLAY	LED	Power on, Backup, Battery Defect, Site Wiring Fault	
AUDIBLE ALARM	Battery Mode	Sounding every 10 seconds	
	Battery Discharge nearly shutdown	Sounding every second	
	Overload	Sounding every 0.5 seconds	
	Fault	Continuously Sounding	
PROTECTION	Full Protection	Overload, Deep Discharge, Overcharge, Short Circuit Protection RJ 11 Modem/Telephone Protection (Two Wires Single Line)	
PHYSICAL	Dimension (DxWxH)	297x130x83.5 (mm)	
	Net Weight	3kgs	3.3kgs
	Outlets	6 (3 for bypass, 3 for back up)	
ENVIRONMENT	Operation Temperature	0-40°C	
	Operation Humidity	20% - 90%	



Global Direct Electronics Outlet LLC.

Address: 15942 D Los Serranos Country Club Dr. #118, Chino Hills, CA 91709, USA

E-Mail: sales@DirectUPS.com

Phone: 909-930-2724, Fax: 909-923-2535

Homepage: www.DirectUPS.com